

DECLARATION OF PERFORMANCE according to Regulation (EC) 305/2011 Nº 1-1-2-CPR-2019

1.Unique identification code of the product-type:

Area code 27 -roomheaters fired by solid fuel

(EN 13240:2001/A2:2004/AC:2007)

Rubin Lux

2.Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11 (4):

Serial № (see rating label on the product).

3.Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Freestanding fireplace without hot water supply, for intermittent burning with firedoors closed, intended for rooms heating

4.Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11 (5):

Victoria-05 Ltd.

1B Ivan Momchilov Str.,5100 Gorna Oryahovitsa Republic of Bulgaria, E-mail: info@v05.bg

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 (2):

6.System or systems of assessment and verification of constancy of performance of the construction product as set

System 3

7.In case of the declaration of performance concerning a construction product covered by a harmonised standard:

Kontrol 94 Ltd.

2 Mladost Str., 5100 Gorna Oryahovitsa Republic of Bulgaria, Body: NB1879 Test report: NB 1879-K-19-2017

8.Declared performance:

out in Annex V:

Harmonized technical specification	EN 13240:2001/A2:2004/AC:2007	
Essential characteristics	Performance	
Fire safety		
Reaction to fire	A1	
Distance to combustible materials	Minimum distances, in mm sides=400 rear=600 front=1000	
Risk of burning fuel falling out	Pass	Sec. Casa Color Sec. Sec. Sec.
Emission of combustion products	CO [0,0921%] -wood;	
Surface temperature	Pass (operating tool)	-11.8000 - 21.
Electrical safety	NPD	
Cleanability	Pass	381187777
Maximum water operating pressure	- bar	
Flue gas temperature at nominal heat output	T [237°C] -wood;	3831
Mechanical resistance (to carry a chimney/flue)	NPD	
Thermal output		
Nominal heat output	13 kW -wood;	
Room heating output	13 kW -wood;	
Water heating output	- kW	
Energy efficiency	η [75,11%] -wood;	200 80021

Emission of combustion products	dust [36,5mg/m³] -wood;	18.0
	NOx [99,74mg/m³] -wood;	14 104/88 10
	CxHy [71,17mg/m³] -wood;	

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

01.04.2019 Gorna Oryahovitsa Manager:

(Plamen Stoyanov)

ODAXOBVILO X

VICTORIA

0